

# APPLICATOR TANKS

## ELLIPTICAL TANKS

Gallons	Diameter	Height	Length	Part No.	Outlet Specs	FOB
300	48"	30"	72"	1471--	U - 10" Lid	C
400	48"	39"	72"	1241--	U - 10" Lid	C
525	58"	36"	81"	1481--	U - 10" Lid	L,C
850	68"	44"	93"	1501--	U - 10" Lid	L
1025	78"	47"	93 1/2"	1491--	U - 10" Lid	L
1300	86"	66"	89"	1001--	Q - 18" Lid	L

OUTLET LEGEND: U = No holes or fittings. Fittings can be ordered separately.



### FEATURES:

- Molded-in gallonage markers (indicators).
- Low profile for ease of transport.
- Bottom sumps and recessed end flat spots.
- UV inhibitors are molded in for longer life.

## CHAMPION SPRAYER TANKS

Gallons	Diameter	Height	Length	Part No.	Outlet Specs	FOB
300	46"	33"	64 1/2"	134--	C	L
500	57"	38 1/2"	77"	138--	C	L

OUTLET LEGEND: C = 10" FILL, TWO 1 1/4" Outlets, one with anti-vortex.



### FEATURES:

- Molded-in gallonage markers (indicators).
- Unique design excellent for custom applications.
- Bottom sumps for ease of draining.
- UV inhibitors are molded in for longer life.

## SIDEMOUNT/TRIM-VUE TANKS

Gallons	Diameter	Height	Length	Part No.	Outlet Specs	FOB
200 TV	32"	42 1/2"	48"	127--	C	L
200 STV	24"	45 1/2"	59"	126--	C	C
250 STV	24"	59"	59 3/4"	118--	C	C
260 TV	31"	48"	54"	131--	C	L

OUTLET LEGEND: C = 10" FILL, TWO 1 1/4" Outlets, one with anti-vortex.



### FEATURES:

- Molded-in gallonage markers (indicators).
- Designed for easy viewing from tractor cab.
- Bottom sumps for better drainage.
- UV inhibitors are molded in for longer life.

## SPHERICAL TANKS

Gallons	Diameter	Height	Part No.	Outlet Specs	FOB
1100	79"	79"	62602--	C	C

OUTLET LEGEND: L = 10" (Lnk) or 18" (CA) lid.



### FEATURES:

- Designed for special applications, reduces sloshing.
- Bottom sump for better drainage.
- UV inhibitors are molded in for longer life.

[www.snydernet.com](http://www.snydernet.com)