

VERTICAL TANKS

Snyder's vertical tanks are versatile enough to use for everything from bulk storage to portable nurse applications. These tough, lightweight tanks come in a variety of styles and sizes from 65 gallons to 16,500 gallons. Snyder vertical tanks feature stable flat bottoms, maximum drainage siphon assemblies and molded-in tie down lugs.

Gallons	Diameter	Height	Manway	Part No.	Outlet Specs	FOB
65	23 1/4"	46"	6"	155--	A	L
120	32"	39"	10"	H15402--	V	C
150	33 3/4"	60"	14"	5710--	U	L
200	39 3/4"	56"	14"	5720--	U	L
200	40"	48"	6"	154--	V	L
200	33"	67"	10"	802--	E	M
205	42"	43"	10"	H15404--	V	C
300	35"	80"	10"	163--	E	M
310	42"	60"	10"	H16302--	N1	C
360	48"	51"	10"	H16303--	N1	C
400	45"	64"	18"	174--	N2	L
550	64"	46"	18"	806--	N2	P,M
550	64"	47"	18"	182--	N2	L,C
550	48"	74"	18"	180--	N2	L,M,P,C
710	60"	68"	18"	H17002	N2	C
850	48"	118"	18"	181--	N2	L,M,P
1000	60"	89"	18"	H18301--	N2	C
1100	64"	91"	18"	183--	N2	L,M,P
1100	86"	57"	10"	171--	I	L,P,C
1100	86"	86"	57"	81200--	I	M
1500	86"	74"	10"	177--	I	L,P,C
1500	86"	74"	18"	81201--	I	M
1550	64"	125"	18"	184--	N2	L,M,P
1650	86"	80"	10"	178--	I	L,P
2000	96"	84"	18"	H50501--	N2	C
2000	90"	88"	18"	5050--	N2	L,P
2000	90"	88"	18"	813--	N2	M
2100	102"	72"	18"	10018--	N2	P
2500	90"	107"	18"	5090--	N2	L,P
2500	90"	107"	18"	81400--	N2	M
2600	96"	98"	18"	H50904--	N2	C

FEATURES:

- Heavy duty bolted fittings standard on 550 gallon and above to reduce threat of fitting loosening during use.
- Fitting compatible siphon tubes to allow bottom fill of tank.
- Molded-in tie downs for securing and lift lugs for easy movement.
- UV inhibitors molded in for longer tank life.

See next page for outlet specs table.



www.snydernet.com

VERTICAL TANKS

VERTICAL						
Gallons	Diameter	Height	Manway	Part No.	Outlet Specs	FOB
3000	96"	112"	18"	H5130--	H	C
3000	90"	127"	18"	5130--	H	L,P
3000	90"	126"	18"	8160--	H	M
3000	102"	97"	18"	74100--	H	L,P,C
4000	102"	131"	18"	8190--	H	M
4100	102"	130"	18"	736--	H	P
4100	120"	100"	18"	820--	H	M
4300	120"	104"	18"	H7420--	H	C
4400	90"	183"	18"	5210--	H	L
4500	102"	143"	18"	7420--	H	L
4700	102"	159"	18"	H74202--	H	C
5000	102"	156"	18"	10020--	H	P
5000	120"	116"	18"	H70001--	H	C
5000	102"	161"	18"	8210--	H	M
5400	142 1/2"	91"	18"	H70002--	H	C
5600	142"	102"	18"	5250--	H	P
6000	102"	188"	18"	7430--	H	L,P,C
6000	120"	132"	18"	7000--	H	L,P
6300	120"	140"	18"	8220--	H	M
6500	120"	145"	18"	H7140--	H	C
6600	120"	153"	18"	H53001--	H	C
6900	120"	154"	18"	7140--	H	L,P
7600	144"	123"	18"	H53002--	H	C
7650	142"	123"	18"	5300--	H	L
7800	120"	176"	18"	10032--	H	C
7900	120"	176"	18"	7370--	H	L
8300	120"	185"	18"	H53003--	H	C
8900	120"	194"	18"	7400--	H	L
9800	120"	215"	18"	7450--	H	L
10500	142"	169"	18"	5330--	H	L,P
10000	142 1/2"	161"	18"	H53301--	H	C
11000	142 1/2"	177"	18"	10053--	H	C
12500	142"	199"	18"	5350--	U/W	L
15000	142"	235"	18"	5370--	U/W	L
16500	142"	259"	18"	5380--	U/W	L

FEATURES:

- Heavy duty bolted fittings standard on 550 gallon and above to reduce threat of fitting loosening during use.
- Fitting compatible siphon tubes to allow bottom fill of tank.
- Molded-in tie downs for securing and lift lugs for easy movement.
- UV inhibitors molded in for longer tank life.

OUTLET SPECS:

- A = 6" fill, one 3/4" outlet with anti-vortex.
 B = 8" fill, one 1 1/4" outlet.
 E = 10" fill, one 2" HD outlet with siphon tube.
 I = 10" fill, one 2" bolted with siphon tube.
 H = 18" manway, one 3" bolted fitting with siphon tube.
 N1 = 18" manway, one 2" HD outlet with siphon tube.
 N2 = 18" manway, one 2" bolted outlet with siphon tube.
 U = No holes or fittings.
 Fittings can be ordered separately.
 V = 6" screw-on cap, one 1 1/4" outlet fitting.
 W = 18" manway.