

VERTICAL TANKS

Snyder's vertical tanks are versatile enough to use for everything from bulk storage to portable nurse applications. These tough, lightweight tanks come in a variety of styles and sizes from 65 gallons to 16,500 gallons. Snyder vertical tanks feature stable flat bottoms, maximum drainage siphon assemblies and molded-in tie down lugs.

| Gallons | Diameter | Height | Manway | Part No. | Outlet Specs | FOB |
|---------|----------|--------|--------|----------|--------------|---------|
| 65 | 23 1/4" | 46" | 6" | 155-- | A | L |
| 120 | 32" | 39" | 10" | H15402-- | V | C |
| 150 | 33 3/4" | 60" | 14" | 5710-- | U | L |
| 200 | 39 3/4" | 56" | 14" | 5720-- | U | L |
| 200 | 40" | 48" | 6" | 154-- | V | L |
| 200 | 33" | 67" | 10" | 802-- | E | M |
| 205 | 42" | 43" | 10" | H15404-- | V | C |
| 300 | 35" | 80" | 10" | 163-- | E | M |
| 310 | 42" | 60" | 10" | H16302-- | N1 | C |
| 360 | 48" | 51" | 10" | H16303-- | N1 | C |
| 400 | 45" | 64" | 18" | 174-- | N2 | L |
| 550 | 64" | 46" | 18" | 806-- | N2 | P,M |
| 550 | 64" | 47" | 18" | 182-- | N2 | L,C |
| 550 | 48" | 74" | 18" | 180-- | N2 | L,M,P,C |
| 710 | 60" | 68" | 18" | H17002 | N2 | C |
| 850 | 48" | 118" | 18" | 181-- | N2 | L,M,P |
| 1000 | 60" | 89" | 18" | H18301-- | N2 | C |
| 1100 | 64" | 91" | 18" | 183-- | N2 | L,M,P |
| 1100 | 86" | 57" | 10" | 171-- | I | L,P,C |
| 1100 | 86" | 86" | 57" | 81200-- | I | M |
| 1500 | 86" | 74" | 10" | 177-- | I | L,P,C |
| 1500 | 86" | 74" | 18" | 81201-- | I | M |
| 1550 | 64" | 125" | 18" | 184-- | N2 | L,M,P |
| 1650 | 86" | 80" | 10" | 178-- | I | L,P |
| 2000 | 96" | 84" | 18" | H50501-- | N2 | C |
| 2000 | 90" | 88" | 18" | 5050-- | N2 | L,P |
| 2000 | 90" | 88" | 18" | 813-- | N2 | M |
| 2100 | 102" | 72" | 18" | 10018-- | N2 | P |
| 2500 | 90" | 107" | 18" | 5090-- | N2 | L,P |
| 2500 | 90" | 107" | 18" | 81400-- | N2 | M |
| 2600 | 96" | 98" | 18" | H50904-- | N2 | C |

FEATURES:

- Heavy duty bolted fittings standard on 550 gallon and above to reduce threat of fitting loosening during use.
- Fitting compatible siphon tubes to allow bottom fill of tank.
- Molded-in tie downs for securing and lift lugs for easy movement.
- UV inhibitors molded in for longer tank life.

See next page for outlet specs table.



VERTICAL TANKS

| VERTICAL | | | | | | |
|----------|----------|--------|--------|----------|--------------|-------|
| Gallons | Diameter | Height | Manway | Part No. | Outlet Specs | FOB |
| 3000 | 96" | 112" | 18" | H5130-- | H | C |
| 3000 | 90" | 127" | 18" | 5130-- | H | L,P |
| 3000 | 90" | 126" | 18" | 8160-- | H | M |
| 3000 | 102" | 97" | 18" | 74100-- | H | L,P,C |
| 4000 | 102" | 131" | 18" | 8190-- | H | M |
| 4100 | 102" | 130" | 18" | 736-- | H | P |
| 4100 | 120" | 100" | 18" | 820-- | H | M |
| 4300 | 120" | 104" | 18" | H7420-- | H | C |
| 4400 | 90" | 183" | 18" | 5210-- | H | L |
| 4500 | 102" | 143" | 18" | 7420-- | H | L |
| 4700 | 102" | 159" | 18" | H74202-- | H | C |
| 5000 | 102" | 156" | 18" | 10020-- | H | P |
| 5000 | 120" | 116" | 18" | H70001-- | H | C |
| 5000 | 102" | 161" | 18" | 8210-- | H | M |
| 5400 | 142 1/2" | 91" | 18" | H70002-- | H | C |
| 5600 | 142" | 102" | 18" | 5250-- | H | P |
| 6000 | 102" | 188" | 18" | 7430-- | H | L,P,C |
| 6000 | 120" | 132" | 18" | 7000-- | H | L,P |
| 6300 | 120" | 140" | 18" | 8220-- | H | M |
| 6500 | 120" | 145" | 18" | H7140-- | H | C |
| 6600 | 120" | 153" | 18" | H53001-- | H | C |
| 6900 | 120" | 154" | 18" | 7140-- | H | L,P |
| 7600 | 144" | 123" | 18" | H53002-- | H | C |
| 7650 | 142" | 123" | 18" | 5300-- | H | L |
| 7800 | 120" | 176" | 18" | 10032-- | H | C |
| 7900 | 120" | 176" | 18" | 7370-- | H | L |
| 8300 | 120" | 185" | 18" | H53003-- | H | C |
| 8900 | 120" | 194" | 18" | 7400-- | H | L |
| 9800 | 120" | 215" | 18" | 7450-- | H | L |
| 10500 | 142" | 169" | 18" | 5330-- | H | L,P |
| 10000 | 142 1/2" | 161" | 18" | H53301-- | H | C |
| 11000 | 142 1/2" | 177" | 18" | 10053-- | H | C |
| 12500 | 142" | 199" | 18" | 5350-- | U/W | L |
| 15000 | 142" | 235" | 18" | 5370-- | U/W | L |
| 16500 | 142" | 259" | 18" | 5380-- | U/W | L |

FEATURES:

- Heavy duty bolted fittings standard on 550 gallon and above to reduce threat of fitting loosening during use.
- Fitting compatible siphon tubes to allow bottom fill of tank.
- Molded-in tie downs for securing and lift lugs for easy movement.
- UV inhibitors molded in for longer tank life.

OUTLET SPECS:

- A = 6" fill, one 3/4" outlet with anti-vortex.
 B = 8" fill, one 1 1/4" outlet.
 E = 10" fill, one 2" HD outlet with siphon tube.
 I = 10" fill, one 2" bolted with siphon tube.
 H = 18" manway, one 3" bolted fitting with siphon tube.
 N1 = 18" manway, one 2" HD outlet with siphon tube.
 N2 = 18" manway, one 2" bolted outlet with siphon tube.
 U = No holes or fittings.
 Fittings can be ordered separately.
 V = 6" screw-on cap, one 1 1/4" outlet fitting.
 W = 18" manway.

